

## FS516

### CHIMANGO 2 - DOUBLE LANYARD WITH ENERGY ABSORBER

The **FALL SAFE® FS516 - CHIMANGO 2 DOUBLE LANYARD WITH ENERGY ABSORBER** is a double lanyard made with 25mm polyester webbing and an energy absorber pack that limits impact force below 6kN. The connectors to be assembled can be selected considering the customer needs and the field of application requirement.



#### CONNECTOR COMBINATIONS



EAN CODE	COMBINATIONS	~WEIGHT (KG)	EAN CODE	COMBINATIONS	~WEIGHT (KG)
5605423700299	1.5M	0,830	5605423752526	LE-1.5M	2,234
5605423700275	1M	0,290	5605423752588	LE-1M	1,704
5605423700268	2M	1,370	5605423700923	LL-1.5M	1,534
5605423752564	HE-1.5M	2,294	5605423752571	LL-1M	1,004
5605423752625	HE-1M	1,764	5605423700756	LL-2M	2,064
5605423752533	HH-1.5M	1,654	5605423700930	LM-1.5M	1,594
5605423752595	HH-1M	1,124	5605423700947	LM-1M	1,064
5605423752540	HM-1.5M	1,654	5605423700954	LM-2M	2,124
5605423752601	HM-1M	1,124	5605423700763	LN-1.5M	1,214
5605423752557	HN-1.5M	1,914	5605423700855	LN-1M	0,684
5605423752618	HN-1M	1,384	5605423700961	LN-2M	1,744

#### APPLICATIONS

Construction | Roof works | Scaffolding | Riggers | Access platforms | Wood poles



#### STANDARDS

CE EN354:2010  
EN355:2002

## FS516-LN

## CHIMANGO 2 - DOUBLE LANYARD WITH ENERGY ABSORBER

### FEATURES



### PHYSICAL PROPERTIES

Materials	PES - Polyester   PVC - polyvinyl chloride   Steel (zinc-plated)
Webbing	100% polyester   Breaking strenght (min.) 3750 kg   Weight 80g/ m   Thickness 3 mm
Energy absorber	100% polyester with heat shrink sleeve covering   Limits arrest force below 6 kN

### OTHER INFORMATION

Device lifespan	10 years
Max. Load	<100 Kg
Inspection requirement	Yearly
Traceability	Serial Number/ QR Code
Manual Instructions	<a href="http://www.fallsafe-online.com">www.fallsafe-online.com</a>   +351 252 480 060