

# DATASHEET

## DEUS ONE



### GENERAL

Art.Nr:	SET-DEUS-SEAL-00-100	Standards:	ANSI Z359.4:2013,EN 341:2011/1D
GTIN:	4030281017455	Net weight:	5.51 kg
E-class number:	40-02-01-06	Gross weight:	5.51 kg
Customs tariff number:	84798997		

# DATASHEET

## DEUS ONE

The DEUS ONE is a personal, fully automatic self-evacuation device. The very small, handy format offers intuitive operation in emergency situations and is ready-to-use due to its configuration with rope and steel carabiners. Without any necessary additional intervention in the abseiling process, even injured or unconscious persons arrive safely on the ground. The extremely compact and lightweight hybrid rope is only 5.9mm thick and heat-resistant up to 450°C. The set is maximally protected from moisture in a Sealpac packaging and can thus achieve a 15-year service life. All components are packed very practically in a compact, protective bag with adjustable straps, making it easy to take to any workplace.

- the smallest, fully automatic self-evacuation device on the market
- compact to carry on the person
- user weight range: 60kg -140kg

### FEATURES

Application areas:	Wind energy
Colour:	Black, polyethylene_terephthalate
Lifting function:	No
Max. Abseil speed:	2.00 m/s
Maximum compatible rope diameter:	5.90 mm
Maximum load 1 person:	140.00 kg
Maximum lifetime:	15 years
Maximum number of persons:	1
Maximum load:	140.00 kg
Min. abseiling speed:	0.50 m/s
Minimum compatible rope diameter:	5.90 mm
Panic function:	No
Rescue function:	No

### DIMENSIONS

Rope length:	100.00 m
--------------	----------

### MATERIAL

Material:	Stainless Steel, Polyamide
-----------	----------------------------

# DATASHEET

## DEUS ONE



### GENERAL

Art.Nr:	SET-DEUS-SEAL-00-160	Standards:	ANSI Z359.4:2013,EN 341:2011/1D
GTIN:	4030281018087	Net weight:	7.95 kg
E-class number:	40-02-01-06	Gross weight:	7.95 kg
Customs tariff number:	84798997		

# DATASHEET

## DEUS ONE

The DEUS ONE is a personal, fully automatic self-evacuation device. The very small, handy format offers intuitive operation in emergency situations and is ready-to-use due to its configuration with rope and steel carabiners. Without any necessary additional intervention in the abseiling process, even injured or unconscious persons arrive safely on the ground. The extremely compact and lightweight hybrid rope is only 5.9mm thick and heat-resistant up to 450°C. The set is maximally protected from moisture in a Sealpac packaging and can thus achieve a 15-year service life. All components are packed very practically in a compact, protective bag with adjustable straps, making it easy to take to any workplace.

- the smallest, fully automatic self-evacuation device on the market
- compact to carry on the person
- user weight range: 60kg -140kg

### FEATURES

Application areas:	Wind energy
Colour:	Black, polyethylene_terephthalate
Lifting function:	No
Max. Abseil speed:	2.00 m/s
Maximum compatible rope diameter:	5.90 mm
Maximum load 1 person:	140.00 kg
Maximum lifetime:	15 years
Maximum number of persons:	1
Maximum load:	140.00 kg
Min. abseiling speed:	0.50 m/s
Minimum compatible rope diameter:	5.90 mm
Panic function:	No
Rescue function:	No

### DIMENSIONS

Rope length:	160.00 m
--------------	----------

### MATERIAL

Material:	Stainless Steel, Polyamide
-----------	----------------------------

# DATASHEET

## DEUS ONE



### GENERAL

Art.Nr:	SET-DEUS-SEAL-00-200	Standards:	ANSI Z359.4:2013,EN 341:2011/1D
GTIN:	4030281017387	Net weight:	9.45 kg
E-class number:	40-02-01-06	Gross weight:	9.45 kg
Customs tariff number:	84798997		

# DATASHEET

## DEUS ONE

The DEUS ONE is a personal, fully automatic self-evacuation device. The very small, handy format offers intuitive operation in emergency situations and is ready-to-use due to its configuration with rope and steel carabiners. Without any necessary additional intervention in the abseiling process, even injured or unconscious persons arrive safely on the ground. The extremely compact and lightweight hybrid rope is only 5.9mm thick and heat-resistant up to 450°C. The set is maximally protected from moisture in a Sealpac packaging and can thus achieve a 15-year service life. All components are packed very practically in a compact, protective bag with adjustable straps, making it easy to take to any workplace.

- the smallest, fully automatic self-evacuation device on the market
- compact to carry on the person
- user weight range: 60kg -140kg

### FEATURES

Application areas:	Wind energy
Colour:	Black, polyethylene_terephthalate
Lifting function:	No
Max. Abseil speed:	2.00 m/s
Maximum compatible rope diameter:	5.90 mm
Maximum load 1 person:	140.00 kg
Maximum lifetime:	15 years
Maximum number of persons:	1
Maximum load:	140.00 kg
Min. abseiling speed:	0.50 m/s
Minimum compatible rope diameter:	5.90 mm
Panic function:	No
Rescue function:	No

### DIMENSIONS

Rope length:	200.00 m
--------------	----------

### MATERIAL

Material:	Stainless Steel, Polyamide
-----------	----------------------------

# DATASHEET

## DEUS ONE



### GENERAL

Art.Nr:	SET-DEUS-SEAL-00-65	Standards:	ANSI Z359.4:2013,EN 341:2011/1D
GTIN:	4030281017509	Net weight:	4.46 kg
E-class number:	40-02-01-06	Gross weight:	4.46 kg
Customs tariff number:	84798997		

# DATASHEET

## DEUS ONE

The DEUS ONE is a personal, fully automatic self-evacuation device. The very small, handy format offers intuitive operation in emergency situations and is ready-to-use due to its configuration with rope and steel carabiners. Without any necessary additional intervention in the abseiling process, even injured or unconscious persons arrive safely on the ground. The extremely compact and lightweight hybrid rope is only 5.9mm thick and heat-resistant up to 450°C. The set is maximally protected from moisture in a Sealpac packaging and can thus achieve a 15-year service life. All components are packed very practically in a compact, protective bag with adjustable straps, making it easy to take to any workplace.

- the smallest, fully automatic self-evacuation device on the market
- compact to carry on the person
- user weight range: 60kg -140kg

### FEATURES

Application areas:	Wind energy
Colour:	Black, polyethylene_terephthalate
Lifting function:	No
Max. Abseil speed:	2.00 m/s
Maximum compatible rope diameter:	5.90 mm
Maximum load 1 person:	140.00 kg
Maximum lifetime:	15 years
Maximum number of persons:	1
Maximum load:	140.00 kg
Min. abseiling speed:	0.50 m/s
Minimum compatible rope diameter:	5.90 mm
Panic function:	No
Rescue function:	No

### DIMENSIONS

Rope length:	65.00 m
--------------	---------

### MATERIAL

Material:	Stainless Steel, Polyamide
-----------	----------------------------