

DATASHEET

GRYPHON ASCENDER



GENERAL

Art.Nr:	G-1176-L/XL	Standards:	EN 358:2018, EN 361:2002, EN 813:2008
GTIN:	8057733309001	Net weight:	2.39 kg
E-class number:	40-02-01-02	Gross weight:	2.39 kg
Customs tariff number:	63079098		

DATASHEET

GRYPHON ASCENDER

Comfortable and ergonomic harness with six attachment points specifically developed for rope access work and equipped with a triangular quick-link and with CHEST ASCENDER+ ventral rope clamp, for maximum ease of use in rope manoeuvres.

Main features:

- close-fitting construction and wide lumbar support belt with breathable mesh padding for optimal comfort during prolonged suspensions;
- contoured shoulder straps with shape optimized to avoid neck chafing;
- shoulder strap equipped with quick-release buckle;
- leg-loop quick-release buckles with indicator for correct insertion;
- leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area;
- adjustable rear straps that allow the leg loops to be moved along the legs;
- large EN 361 sternal attachment point to facilitate rescue operations;
- EN 358 lateral attachment points with two positions: outward-facing when in use (work mode); inward-folded when not in use (stand-by mode) in order not to hamper the operator's movements;
- EN 361 dorsal attachment point designed to avoid accidentally getting snagged, especially while working in confined spaces;
- attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;
- dedicated loop for quick-link, to be used for the addition of a ventral rope clamp in combination with appropriate straps;
- two horizontal straps positioned on the

FEATURES

Attachment points:	Sternal aluminium attachment point, Dorsal steel attachment point, Side aluminium attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 10 kg:	4
Application areas:	Arborists, RBA rigging, Emergency, Rescue
Colour:	Black, Orange
Harness features:	Lanyard parking ring, Integrated chest ascender
Hand wash:	40 °C
Maximum body height:	205 cm
Maximum lifetime:	10 years
Maximum hip size:	120 cm
Maximum leg size:	70 cm
Maximum temperature:	60 °C
Minimum body height:	180 cm
Minimum hip size:	80 cm
Minimum leg size:	55 cm
Minimum temperature:	-20 °C
Padding:	Back padding, Leg paddings, Shoulder paddings
Buckles:	stick_buckle, click_buckle

DATASHEET

GRYPHON ASCENDER

shoulder straps and exclusively intended for the insertion of HOOK REST support;

- two dedicated loops for the connection of a work-positioning seat;
- four large gear-loops, six loops for the tool-holder pouch and four slots for carrying-tools carabiners;
- maximum load: 140 kg.

Adjusting buckles:	Adjusting buckles shoulders, Adjusting buckles hips, Adjusting buckles legs
--------------------	---

DIMENSIONS

Size:	L-XL
-------	------

MATERIAL

Material:	Polyamide, Polyester, Polyethylene, Steel, Aluminium
-----------	--

DATASHEET

GRYPHON ASCENDER**GENERAL**

Art.Nr:	G-1176-M/L	Standards:	EN 358:2018, EN 361:2002, EN 813:2008
GTIN:	8057733308998	Net weight:	2.29 kg
E-class number:	40-02-01-02	Gross weight:	2.29 kg
Customs tariff number:	63079098		

DATASHEET

GRYPHON ASCENDER

Comfortable and ergonomic harness with six attachment points specifically developed for rope access work and equipped with a triangular quick-link and with CHEST ASCENDER+ ventral rope clamp, for maximum ease of use in rope manoeuvres.

Main features:

- close-fitting construction and wide lumbar support belt with breathable mesh padding for optimal comfort during prolonged suspensions;
- contoured shoulder straps with shape optimized to avoid neck chafing;
- shoulder strap equipped with quick-release buckle;
- leg-loop quick-release buckles with indicator for correct insertion;
- leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area;
- adjustable rear straps that allow the leg loops to be moved along the legs;
- large EN 361 sternal attachment point to facilitate rescue operations;
- EN 358 lateral attachment points with two positions: outward-facing when in use (work mode); inward-folded when not in use (stand-by mode) in order not to hamper the operator's movements;
- EN 361 dorsal attachment point designed to avoid accidentally getting snagged, especially while working in confined spaces;
- attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;
- dedicated loop for quick-link, to be used for the addition of a ventral rope clamp in combination with appropriate straps;
- two horizontal straps positioned on the

FEATURES

Attachment points:	Sternal aluminium attachment point, Dorsal steel attachment point, Side aluminium attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 10 kg:	4
Application areas:	Arborists, RBA rigging, Emergency, Rescue
Colour:	Black, Orange
Harness features:	Lanyard parking ring, Integrated chest ascender
Hand wash:	40 °C
Maximum body height:	190 cm
Maximum lifetime:	10 years
Maximum hip size:	100 cm
Maximum leg size:	60 cm
Maximum temperature:	60 °C
Minimum body height:	170 cm
Minimum hip size:	70 cm
Minimum leg size:	50 cm
Minimum temperature:	-20 °C
Padding:	Back padding, Leg paddings, Shoulder paddings
Buckles:	stick_buckle, click_buckle

DATASHEET

GRYPHON ASCENDER

shoulder straps and exclusively intended for the insertion of HOOK REST support;

- two dedicated loops for the connection of a work-positioning seat;
- four large gear-loops, six loops for the tool-holder pouch and four slots for carrying-tools carabiners;
- maximum load: 140 kg.

Adjusting buckles:	Adjusting buckles shoulders, Adjusting buckles hips, Adjusting buckles legs
--------------------	---

DIMENSIONS

Size:	M-L
-------	-----

MATERIAL

Material:	Polyamide, Polyester, Polyethylene, Steel, Aluminium
-----------	--

DATASHEET

GRYPHON ASCENDER



GENERAL

Art.Nr:	G-1176-S/M	Standards:	EN 358:2018, EN 361:2002, EN 813:2008
GTIN:	8057733308981	Net weight:	2.20 kg
E-class number:	40-02-01-02	Gross weight:	2.20 kg
Customs tariff number:	63079098		

DATASHEET

GRYPHON ASCENDER

Comfortable and ergonomic harness with six attachment points specifically developed for rope access work and equipped with a triangular quick-link and with CHEST ASCENDER+ ventral rope clamp, for maximum ease of use in rope manoeuvres.

Main features:

- close-fitting construction and wide lumbar support belt with breathable mesh padding for optimal comfort during prolonged suspensions;
- contoured shoulder straps with shape optimized to avoid neck chafing;
- shoulder strap equipped with quick-release buckle;
- leg-loop quick-release buckles with indicator for correct insertion;
- leg-loops designed with targeted panel construction to ensure optimal comfort while in suspension by relieving pressure in the groin area;
- adjustable rear straps that allow the leg loops to be moved along the legs;
- large EN 361 sternal attachment point to facilitate rescue operations;
- EN 358 lateral attachment points with two positions: outward-facing when in use (work mode); inward-folded when not in use (stand-by mode) in order not to hamper the operator's movements;
- EN 361 dorsal attachment point designed to avoid accidentally getting snagged, especially while working in confined spaces;
- attachment point on the rear of the waistbelt, marked by the letter R and exclusively intended for the connection of a restraint lanyard;
- dedicated loop for quick-link, to be used for the addition of a ventral rope clamp in combination with appropriate straps;
- two horizontal straps positioned on the

FEATURES

Attachment points:	Sternal aluminium attachment point, Dorsal steel attachment point, Side aluminium attachment point, Sit harness aluminium attachment point, Restraint polyester attachment point
Number of material loops 10 kg:	4
Application areas:	Arborists, RBA rigging, Emergency, Rescue
Colour:	Black, Orange
Harness features:	Lanyard parking ring, Integrated chest ascender
Hand wash:	40 °C
Maximum body height:	185 cm
Maximum lifetime:	10 years
Maximum hip size:	80 cm
Maximum leg size:	55 cm
Maximum temperature:	60 °C
Minimum body height:	160 cm
Minimum hip size:	60 cm
Minimum leg size:	45 cm
Minimum temperature:	-20 °C
Padding:	Back padding, Leg paddings, Shoulder paddings
Buckles:	stick_buckle, click_buckle

DATASHEET

GRYPHON ASCENDER

shoulder straps and exclusively intended for the insertion of HOOK REST support;

- two dedicated loops for the connection of a work-positioning seat;
- four large gear-loops, six loops for the tool-holder pouch and four slots for carrying-tools carabiners;
- maximum load: 140 kg.

Adjusting buckles:	Adjusting buckles shoulders, Adjusting buckles hips, Adjusting buckles legs
--------------------	---

DIMENSIONS

Size:	S-M
-------	-----

MATERIAL

Material:	Polyamide, Polyester, Polyethylene, Steel, Aluminium
-----------	--
