

3M™ DBI-SALA® ExoFit™ XE200 Comfort Positioning Safety Harness with auto-locking quick connect buckles

Part number(s):

- 1112729 (Size 1)
- 1112730 (Size 2)
- 1112731 (Size 3)

Description

Sub-brand:	DBI-SALA®
Industry:	Construction, General Industrial, General Manufacturing, Transportation
Applications:	Climbing, Positioning

Features

Rear fall arrest attachment point:	<ul style="list-style-type: none"> • Large stand-up D-ring – Aluminium - blue anodisation
Front fall arrest attachment point:	<ul style="list-style-type: none"> • Standard D-ring – Aluminium - blue anodisation
Work positioning Attachment points:	<ul style="list-style-type: none"> • Large cranked D-ring – Aluminium - blue anodisation
Leg Buckles:	<ul style="list-style-type: none"> • Auto-locking quick connect – Steel - zinc plated/black paint, aluminium - grey anodisation
Chest Buckles:	<ul style="list-style-type: none"> • Quick connect – Steel - zinc plated/black paint, aluminium - grey anodisation
Waist Buckles:	<ul style="list-style-type: none"> • Auto-locking quick connect – Steel - zinc plated/black paint, aluminium - grey anodisation
Adjustment:	<ul style="list-style-type: none"> • Legs, waist, torso • Torso: Revolving adjuster – Steel/aluminium - ratchet buckle
Webbing:	45mm Polyester
Thread:	Polyester
Additional features:	<ul style="list-style-type: none"> • Front & rear fall indicators • Leg, shoulder & waist padding • 2x Auto-resetting/repositionable lanyard keepers • RFID Equipped • Suspension trauma straps • Dedicated personal self-retracting lifeline attachment point
Weight capacity:	140 kg
Standards:	<ul style="list-style-type: none"> • CE EN361:2002; EN358:2019 • UKCA




Front



Back

3M™ DBI-SALA® Fall Arrest Harness sizing chart



Weight

	←.....→	kg
1112729	Size 1	2.85
1112730	Size 2	2.90
1112731	Size 3	2.95

Important notice

The mounting and use of the product described within this document assumes that the user has previous experience of this type of product and that it will be assembled by a competent professional according to product documentation. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M Group (who cannot verify or control these elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for products are determined with the sales contract documents and with the mandatory and applicable law, excluding any other warranty or compensation.

3M Fall Protection

Capital Safety (Northern Europe) Limited
3M Centre, Cain Road
Bracknell, Berkshire, RG12 8HT, UK

Capital Safety Group (EMEA)
Le Broc Center, Bâtiment A, Z.1. 1re Avenue – BP15
06511 Carros Le Broc, Cedex, FRANCE

Phone +33(0) 4 83 58 08 08 Email informationfallprotection@mmm.com Web 3M.com/FallProtection

3M, DBI-SALA, ExoFit, Scotchlite, belongs to 3M Company and its affiliates.



Fall Protection