

FS030

JYNX 1 ADJUSTABLE LANYARD ROPE

The **FALL SAFE® FS030 - JYNX 1 ADJUSTABLE LANYARD ROPE** is a single lanyard rope with a length 8-ring adjuster which allows it to go from 1.3 up to 2 meters length. The connectors to be assembled can be selected considering the customer needs and the field of application requirement.



CONNECTOR COMBINATIONS



EAN CODE	COMBINATIONS	~WEIGHT (KG)
5605423800821	No metals	0,381
5605423753325	HH	0,821
5605423753332	HM	0,821
5605423753349	HN	1,081
5605423753318	LE	1,401
5605423731835	LL	0,701
5605423753301	LM	0,761
5605423730913	LN	1,021
5605423730883	ML	0,761
5605423730890	MM	0,821
5605423730906	MN	1,081

APPLICATIONS

Roof works | Scaffolding | Access platforms | Wind turbines | Construction | Wood poles



STANDARDS

CE EN354:2010

FS030-LL JYNX 1 ADJUSTABLE LANYARD ROPE

FEATURES



PHYSICAL PROPERTIES

Materials	Kernmantel Steel (zinc-plated)
Rope	Basic 11mm kernmantel
Energy absorber	N/A

OTHER INFORMATION

Device lifespan	10 years
Max. Load	<100 Kg
Inspection requirement	Yearly
Traceability	Serial Number/ QR Code
Manual Instructions	www.fallsafe-online.com +351 252 480 060

FS802 ZINC-PLATED STEEL OVAL

The **FALL SAFE® FS802 - ZINC PLATED STEEL OVAL** is a screw lock connector in zinc plated steel, with a 18 mm opening and a breaking strength of 25 kN.



EAN CODE	STRENGTH (kN)	OPENING (MM)	~WEIGHT (KG)	STANDARDS
5605423400113	25	18	0,162	CE EN362:2004-B EN12275:1998-H

APPLICATIONS

Telecom towers | Rope access | Roof works | Riggers | Rescue | Construction | Arborism



PHYSICAL PROPERTIES	
Material	Zinc plated steel
Closure	Screw lock
OTHER INFORMATION	
Device lifespan	Undefined*
Inspection requirement	Yearly
Traceability	Serial Number/ Batch number
Manual Instructions	www.fallsafe-online.com +351 252 480 060

*The product's lifetime is considered Undefined, when the products can be used until being rejected during the inspection.