

DATASHEET

PEANUT I



GENERAL

Art.Nr:	HSG-021-1,8-3	Standards:	DIN 19427:2017,EN 360:2002,GS-PS-12: 2019,RFU PPE-R/11.060:2018,RFU PPE-R/11.085:2020,RFU PPE-R/11.124:2020
GTIN:	4030281181934	Net weight:	1.94 kg
E-class number:	40-02-01-03	Gross weight:	1.94 kg
Customs tariff number:	84798997		

DATASHEET

PEANUT I

The compact connecting device PEANUT I with FS90 ST karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The karabiner with an opening width of 59 mm can be used variably and is extremely robust. The fastener is suitable for edges and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in aerial work platforms. Due to the spring-loaded webbing retraction, the person remains safely on the platform even in case of a catapult effect. A red indicator shows when the strap fall arrester has been triggered and provides additional safety. The PEANUT I also serves to secure the stand.

FEATURES

Application areas:	Facades cleaning, Shaft, Mobile Work Platforms
Colour:	Black, Grey, Orange
Edge approved:	Yes
Maximum user weight vertical:	135.00 kg
Maximum lifetime:	10 years
Maximum number of persons:	1
Maximum temperature:	45 °C
Minimum user weight:	50.00 kg
Minimum temperature:	-35 °C

DIMENSIONS

Rope length:	1.80 m
--------------	--------

MATERIAL

Material:	Polyester, Polyamide, Steel, Aluminium
-----------	--