

Data sheet

MILAN 2.0 HUB



GENERAL

Art. no.:	A-028	E-class number:	40-02-01-06
EAN:	4030281155850	Customs no.:	84251900
Standard:	DIN EN 1496-A:2017 DIN EN 341-1A:2011		

Data sheet

MILAN 2.0 HUB

MILAN 2.0 HUB is THE standard rescue device in the industry with additional lifting function. With the help of the hand wheel, the casualty can be lifted over a short distance to release his lanyard and lower him safely. The device is optimised for personal rescue.

Note: When working at height, a suitable rescue concept based on a risk assessment is essential. MILAN offers a wide range of applications for different rescue scenarios. To master these techniques, users must be carefully trained by a SKYLOTEC-certified instructor who has been specially trained on the device.

- THE standard rescue device
 - With additional lifting function
 - User weight of up to 280 kg with redirection
- Intuitive operation due to rope guide and brake in the housing

GENERAL

Internat. standard:
ANSI Z359.4:2013, MEETS CSA Z259.2.3-1B:2012

FEATURES

Colour:	orange / black / white
Abseiling speed:	0,90 m/s
Abseiling height:	500,00 m
Max. service life:	20 Years
Max. number of persons:	2
Rated load:	260 KG
Temperature:	from 60 °C to -35 °C
Suspension element:	KM9
Area of application:	Fire brigade / Rescue / Special Forces, Lift Construction, Power Supplies / -Transmission / Telecommunications, Rope Courses, Wind Energy / Offshore Industry

DIMENSIONS

Weight: 5,01 kg

HARDWARE

Carabiner on anchoring point side:

KOBRA TW

MATERIAL

Material:

Aluminium, Steel, Polyamide
