

DATASHEET

LIFELINE HORIZONTAL



GENERAL

Art.Nr:	L-0329	Standards:	CEN/TS 16415:2013, EN 795-B/C:2012
GTIN:	4030281086406	Net weight:	2.98 kg
E-class number:	40-02-01-90	Gross weight:	2.98 kg
Customs tariff number:	63079010		

DATASHEET

LIFELINE HORIZONTAL

Temporary horizontal securing systems are very popular for assembly work in steel construction, scaffolding and construction in general. LIFELINE HORIZONTAL is a transportable, very quick to assemble and flexible slinging device. It allows two people to work safely over a distance of up to 20 meters. The system's two carabiners are attached to suitable structures such as steel girders, scaffolding frames or concrete columns using slings, for example. The attachment points to be used must be designed for a minimum strength of 11 kN and must not exceed a maximum distance of 20 m

- 20 meters horizontal securing distance
- The structure used must withstand a load of 11 kN
- Flexible horizontal securing system for almost any construction site

FEATURES

Application areas:	Roofers, Steelwork
--------------------	--------------------

Colour:	Black, Orange
---------	---------------

Maximum lifetime:	10 years
-------------------	----------

DIMENSIONS

Useable length:	20.00 m
-----------------	---------

MATERIAL

Material:	Polyester, Steel
-----------	------------------