

DATASHEET

PEANUT I



GENERAL

Art.Nr:	HSG-021-2,5-7	Standards:	EN 360:2002,GS-PS-12:2019,RFU PPE-R/11.060:2018,RFU PPE-R/11.085:2020,RFU PPE-R/11.124:2020
GTIN:	4030281182016	Net weight:	1.93 kg
E-class number:	40-02-01-03	Gross weight:	1.93 kg
Customs tariff number:	84798997		

DATASHEET

PEANUT I

The compact connecting device PEANUT I with the FS64 AL GR karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low. The FS64 AL GR with an opening width of 64 mm is light and yet very robust with a reinforced gate. The fastener is edge-suitable and thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. The 2.5 m long arm makes PEANUT I ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

FEATURES

Application areas:	Scaffolding
Colour:	Black, Grey, Orange
Edge approved:	Yes
Maximum user weight vertical:	135.00 kg
Maximum lifetime:	10 years
Maximum number of persons:	1
Maximum temperature:	45 °C
Minimum user weight:	50.00 kg
Minimum temperature:	-35 °C

DIMENSIONS

Rope length:	2.50 m
--------------	--------

MATERIAL

Material:	Polyester, Polyamide, Steel, Aluminium
-----------	--