

FS222 ULTRA HARNESS

The **FALL SAFE® FS222 - ULTRA HARNESS** is a specifically designed to work at height harness equipped with 2 side D-rings for work positioning, ergonomic support belt, ergonomic backpad, padded legs, lanyard keepers, 6 point size adjustment for perfect fit and a reflex fabric to keep you visible and safer.

The airflow through all the harness layers is assured by the new and improved Croc™ 2.0 padding. This innovation also allows for a lighter and more ergonomic final product, that is extremely comfortable for use for several hours.

With reflective and extra breathable fabric, the FS222 combines the lightness of its composition with the FALL SAFE® quality assurance.



EAN CODE	SIZE	WEIGHT (KG)
5605423570090	S/M	2,258
5605423570106	L/XL	2,283
5605423570113	XXL	2,308

APPLICATIONS

Tower climbing | Telecom towers | Access platforms | Construction
Roof works | Wind turbine | Scaffolding | Wood poles



INTENSITY OF USE

Intensive use



STANDARDS

CE EN361:2002
EN358:1999

FS222 ULTRA HARNESS

FEATURES



PHYSICAL PROPERTIES

Metal parts	Aluminium
Webbing	PES HP Water repellent
D-rings	Dorsal D-ring 2 side D-rings for work positioning
Loops	2 front loops for fall arrest
Buckles	IZY Quick connect buckles
Padding	Croc™ 2.0
Adjustment points	6 points
Fall arrest indicators	Yes

OTHER INFORMATION

Device lifespan	10 years
Max. Load	<140 KG
Inspection requirement	Yearly
Traceability	Serial Number/ RFID/ QR Code
Manual Instructions	www.fallsafe-online.com +351 252 480 060