

DATASHEET PEANUT I F. PLATFORMS



GENERAL

Art.Nr:	HSG-021-1,8-8	DIN 19427:2017,EN 360:2002,GS-PS-12: 2019,RFU PPE-R/11. 060:2018,RFU PPE- R/11.085:2020,RFU PPE-R/11.124:2020	360:2002,GS-PS-12:
GTIN:	4030281197720		
E-class number:	40-02-01-03		
Customs tariff number:	84798997	Net weight:	1.74 kg
		Gross weight:	1.74 kg



DATASHEET

PEANUT I F. PLATFORMS

The compact connecting device PEANUT I with the KOBRA TRI karabiner convinces with its self-retracting arm, which does not restrict the working radius and ensures that the fall height is extremely low.

The small steel trilock

karabiner with a breaking load of 45 kN and an opening width of 22 mm is

characterised above all by its robustness. The fastener is edge-suitable and

thus also serves for horizontal securing. PEANUT I contains the One-4-All damper and is therefore suitable for a very

wide range of user weights from 50

to 135 kilograms. The 1.8 m long arm makes PEANUT I ideal for securing in

aerial work platforms. Due to the springloaded webbing retraction, the person remains safely on the platform even in case

of a catapult effect. A red

indicator shows when the strap fall arrester has been triggered and provides

additional safety. The PEANUT I also serves to secure the stand.

FEATURES

Application areas:	Facades cleaning, Mobile Work Platforms		
Colour:	Black, Grey, Orange		
Edge approved:	Yes		
Maximum user weight vertical:	135.00 kg		
Maximum lifetime:	10 years		
Maximum number of persons:	1		
Maximum temperature:	45 °C		
Minimum user weight:	50.00 kg		
Minimum temperature:	-35 °C		
DIMENSIONS			
Rope length:	1.80 m		

MATERIAL