

DATASHEET

SKYSAFE PRO+**GENERAL**

Art.Nr:	L-0837-1C8
GTIN:	4030281029311
E-class number:	40-02-01-04
Customs tariff number:	56090000

Standards:	EN 354:2010, EN 355:2002, EN 795:2012/B, RFU PPE-R/11.074
Net weight:	2.33 kg
Gross weight:	2.33 kg

DATASHEET

SKYSAFE PRO+

The SKYSAFE PRO+ is a lanyard with flexible arms and ultra-compact webbing fall arrester that covers a weight range from 50 to 150 kg and reduces the force to less than 6 kN with a maximum fall arrest distance of 1.75m. The sewn-in RESCUE LOOPS allow the casualty to be lifted with a rescue device in the event of a fall, relieving the load on the carabiner and facilitating the rescue. Available in four different designs with different carabiner combinations.

- Compact webbing fall arrester for high freedom of movement
- Universally applicable due to wide weight range from 50 to 150 kg
- Quick and easy rescue thanks to integrated RESCUE LOOPS

FEATURES

Application areas: Mobile platforms, Working in confined spaces, Elevator construction, Arborists, lithium_ion, Roofers, Facades cleaning, Flat roof construction, Scaffolding, High Rack storage, Rescue, Off Shore Industry, Emergency, Route construction, Shaft, RBA rigging, Steelwork, Telco energy

Fallindicator:	Yes
Impact force:	6.00 kN
Colour:	Black, polyethylene_terephthalate
Hand wash:	40 °C
Edge approved:	Yes
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C
Rescue loop:	Yes
Lanyard type:	Y-Version

DIMENSIONS

Rope length:	1.80 m
length_lanyard:	1.80 m

DATASHEET

SKYSAFE PRO+

Lanyard rope diameter:	30.00 mm
------------------------	----------

MATERIAL

Material:	Polyester, Polyamide, Aluminium
-----------	---------------------------------
