

# DATASHEET

## DYNAMIX



### GENERAL

Art.Nr:	L-0816-2	Standards:	EN 354:2010,EN 795/B:2012
GTIN:	8056734834253	Net weight:	0.19 kg
E-class number:	40-02-01-90	Gross weight:	0.19 kg
Customs tariff number:	56090000		

# DATASHEET

## DYNAMIX

High strength safety rope, Ø 11 mm dynamic rope.

Main features:

- eyelets with thimbles and double-layer stitching;
- dynamic rope acts as energy absorber for falls of Fall Factor less than 0,5;
- maximum load 100 kg and length up to 2 m.

### FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Maximum temperature:	40 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C

### DIMENSIONS

Rope length:	0.00 m
length_lanyard:	2.00 m

### MATERIAL

Material:	Polyamide
-----------	-----------

# DATASHEET

## DYNAMIX



### GENERAL

Art.Nr:	L-0816-0,6	Standards:	EN 354:2010,EN 795/B:2012
GTIN:	8057733301500	Net weight:	0.08 kg
E-class number:	40-02-01-90	Gross weight:	0.08 kg
Customs tariff number:	56090000		

# DATASHEET

## DYNAMIX

High strength safety rope, Ø 11 mm dynamic rope.

Main features:

- eyelets with thimbles and double-layer stitching;
- dynamic rope acts as energy absorber for falls of Fall Factor less than 0,5;
- maximum load 100 kg and length up to 2 m.

### FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Maximum temperature:	40 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C

### DIMENSIONS

Rope length:	0.00 m
length_lanyard:	0.60 m

### MATERIAL

Material:	Polyamide
-----------	-----------

# DATASHEET

## DYNAMIX



### GENERAL

Art.Nr:	L-0816-0,8	Standards:	EN 354:2010,EN 795/B:2012
GTIN:	8057733301517	Net weight:	0.09 kg
E-class number:	40-02-01-90	Gross weight:	0.09 kg
Customs tariff number:	56090000		

# DATASHEET

## DYNAMIX

High strength safety rope, Ø 11 mm dynamic rope.

Main features:

- eyelets with thimbles and double-layer stitching;
- dynamic rope acts as energy absorber for falls of Fall Factor less than 0,5;
- maximum load 100 kg and length up to 2 m.

### FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Maximum temperature:	40 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C

### DIMENSIONS

Rope length:	0.00 m
length_lanyard:	0.80 m

### MATERIAL

Material:	Polyamide
-----------	-----------

# DATASHEET

## DYNAMIX



### GENERAL

Art.Nr:	L-0816-1	Standards:	EN 354:2010,EN 795/B:2012
GTIN:	8056734834239	Net weight:	0.11 kg
E-class number:	40-02-01-90	Gross weight:	0.11 kg
Customs tariff number:	56090000		

# DATASHEET

## DYNAMIX

High strength safety rope, Ø 11 mm dynamic rope.

Main features:

- eyelets with thimbles and double-layer stitching;
- dynamic rope acts as energy absorber for falls of Fall Factor less than 0,5;
- maximum load 100 kg and length up to 2 m.

### FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Maximum temperature:	40 °C
Minimum tensile strength:	22.00 kN
Minimum temperature:	-35 °C

### DIMENSIONS

Rope length:	0.00 m
length_lanyard:	1.00 m

### MATERIAL

Material:	Polyamide
-----------	-----------



# DATASHEET

## DYNAMIX



### GENERAL

Art.Nr:	L-0816-1,5	Standards:	EN 354:2010,EN 795/B:2012
GTIN:	8056734834246	Net weight:	0.15 kg
E-class number:	40-02-01-90	Gross weight:	0.15 kg
Customs tariff number:	56090000		

# DATASHEET

## DYNAMIX

High strength safety rope, Ø 11 mm dynamic rope.

Main features:

- eyelets with thimbles and double-layer stitching;
- dynamic rope acts as energy absorber for falls of Fall Factor less than 0,5;
- maximum load 100 kg and length up to 2 m.

### FEATURES

Application areas:	Various
--------------------	---------

Fallindicator:	No
----------------	----

Colour:	Black
---------	-------

Hand wash:	40 °C
------------	-------

Edge approved:	No
----------------	----

Maximum lifetime:	10 years
-------------------	----------

Maximum temperature:	40 °C
----------------------	-------

Minimum tensile strength:	22.00 kN
---------------------------	----------

Minimum temperature:	-35 °C
----------------------	--------

### DIMENSIONS

Rope length:	0.00 m
--------------	--------

length_lanyard:	1.50 m
-----------------	--------

### MATERIAL

Material:	Polyamide
-----------	-----------