

DATASHEET

OVX SG



GENERAL

Art.Nr:	H-248	Standards:	EN 12275-B:2013, EN 362-B:2004, UIAA 121
GTIN:	4030281021124	Net weight:	0.06 kg
E-class number:	40-02-01-05	Gross weight:	0.06 kg
Customs tariff number:	76169990		

DATASHEET

OVX SG

Hot-rolled light-alloy oval carabiner with reduced dimensions and screw-lock gate. The OVX SG's compact size of 9.5 cm and curved back make it fit in any hand. This allows a maximize opening of the snapper and improves handling. Thus, it is the optimal companion for work with limited space, for example, for rope and height work and in rescue. The fact that there is no discontinuities in the line between the nose and the interior of the connector also facilitates the insertion and/or release of anchors, tools and ropes. The oval shape of the OVX SG is used for optimal positioning of ropes and tools. Better sliding and wear resistance of the rope is guaranteed by the carabiner thanks to its increased cross-section at the contact points.

- Good handling due to shape and size
- Optimal for work with limited movement space
- Better gliding due to increased cross section

FEATURES

Swivel:	No
Carabiner properties:	Corrosion resistance
Application areas:	Various
Fallindicator:	No
Colour:	Black, polyethylene_terephthalate
Strengths - lengthways:	24.00 kN
Strengths - open:	7.00 kN
Strengths - across:	9.00 kN
Form fit:	Key Lock
Carabiner type:	Type B (EN 362:2004), Type B (EN 12275:2013)
Maximum lifetime:	30 years
Maximum temperature:	40 °C
Minimum temperature:	-30 °C
Standard ANSI:	No
Standard UIAA:	Yes
Anti-twist device:	No
Carabiner clasp:	Screw

DIMENSIONS

Opening width:	17 mm
----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------