



GENERAL

Art.Nr:	L-0688-7,5	Net weight:	0.76 kg
GTIN:	4030281011408	Gross weight:	0.76 kg
E-class number:	40-02-01-90		
Customs tariff number:	56090000		

www.skylotec.com I Datenblatt, 18.10.23



ROPE FOR LORY PRO

The ROPE FOR LORY PRO with RESISTOR carabiner serves as a rope for the SET LORY

PRO. As soon as the rope of your SET LORY PRO needs to be replaced, you can use

this as a spare part. No tools are needed for the replacement.

FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	31.50 kN
Minimum temperature:	-35 °C

um
u





GENERAL

Art.Nr:	L-0688-1,5	Net weight:	0.31 kg
GTIN:	4030281249917	Gross weight:	0.31 kg
E-class number:	40-02-01-90		
Customs tariff number:	56090000		

www.skylotec.com | Datenblatt, 18.10.23



ROPE FOR LORY PRO

The ROPE FOR LORY PRO with RESISTOR carabiner serves as a rope for the SET LORY

PRO. As soon as the rope of your SET LORY PRO needs to be replaced, you can use

this as a spare part. No tools are needed for the replacement.

FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	31.50 kN
Minimum temperature:	-35 °C

length_lanyard:	1.50 m
Lanyard rope diameter:	10.50 mm
MATERIAL	
MATERIAL Material:	Polyamide, Aluminium





GENERAL

Art.Nr:	L-0688-10	Net weight:	1.01 kg
GTIN:	4030281011057	Gross weight:	1.01 kg
E-class number:	40-02-01-90		
Customs tariff number:	56090000		



ROPE FOR LORY PRO

The ROPE FOR LORY PRO with RESISTOR carabiner serves as a rope for the SET LORY

PRO. As soon as the rope of your SET LORY PRO needs to be replaced, you can use

this as a spare part. No tools are needed for the replacement.

FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	31.50 kN
Minimum temperature:	-35 °C

length_lanyard:	10.00 m
Lanyard rope diameter:	10.50 mm
MATERIAL	
Material:	Polyamide, Aluminium





GENERAL

Art.Nr:	L-0688-2	Net weight:	0.38 kg
GTIN:	4030281253457	Gross weight:	0.38 kg
E-class number:	40-02-01-90		
Customs tariff number:	56090000		

www.skylotec.com | Datenblatt, 18.10.23



ROPE FOR LORY PRO

The ROPE FOR LORY PRO with RESISTOR carabiner serves as a rope for the SET LORY

PRO. As soon as the rope of your SET LORY PRO needs to be replaced, you can use

this as a spare part. No tools are needed for the replacement.

FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	31.50 kN
Minimum temperature:	-35 °C

length_lanyard:	2.00 m
Lanyard rope diameter:	10.50 mm
MATERIAL	
MATERIAL Material:	Polyamide, Aluminium





GENERAL

Art.Nr:	L-0688-3	Net weight:
GTIN:	4030281266846	Gross weight:
E-class number:	40-02-01-90	
Customs tariff number:	56090000	

Net weight:	0.50 kg
Gross weight:	0.50 kg



ROPE FOR LORY PRO

The ROPE FOR LORY PRO with RESISTOR carabiner serves as a rope for the SET LORY

PRO. As soon as the rope of your SET LORY PRO needs to be replaced, you can use

this as a spare part. No tools are needed for the replacement.

FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	31.50 kN
Minimum temperature:	-35 °C

length_lanyard:	3.00 m
Lanyard rope diameter:	10.50 mm
MATERIAL	
Material:	Polyamide, Aluminium





GENERAL

Art.Nr:	L-0688-5	Net weight:	0.74 kg
GTIN:	4030281288558	Gross weight:	0.74 kg
E-class number:	40-02-01-90		
Customs tariff number:	56090000		

www.skylotec.com I Datenblatt, 18.10.23



ROPE FOR LORY PRO

The ROPE FOR LORY PRO with RESISTOR carabiner serves as a rope for the SET LORY

PRO. As soon as the rope of your SET LORY PRO needs to be replaced, you can use

this as a spare part. No tools are needed for the replacement.

FEATURES

Application areas:	Various
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	31.50 kN
Minimum temperature:	-35 °C

length_lanyard:	5.00 m
Lanyard rope diameter:	10.50 mm
MATERIAL	
Material:	Polyamide, Aluminium