

DATASHEET

PEANUT Y



GENERAL

Art.Nr:	HSG-022-1,8-6
GTIN:	4030281182078
E-class number:	40-02-01-03
Customs tariff number:	84798997

Standards:	DIN 19427:2017,EN 360:2002,GS-PS-12:2019,RFU PPE-R/11.060:2018,RFU PPE-R/11.085:2020,RFU PPE-R/11.124:2020
Net weight:	3.29 kg
Gross weight:	3.29 kg

DATASHEET

PEANUT Y

The compact connecting device PEANUT Y with the FS64 AL OR karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the drop height is extremely low. The FS64 AL OR GR with an opening width of 64 mm is light and yet very robust with a reinforced gate. The lanyard is perfectly suited for continuous, mutual securing - even at lower heights. The PEANUT Y is edge-suitable and thus also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 1.8 m long arms, the PEANUT Y is ideal for securing in aerial work platforms. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap fall arrester has been released and provides additional safety.

FEATURES

Application areas:	Facades cleaning, High Rack storage, Mobile Work Platforms
Colour:	Black, Grey, Orange
Edge approved:	Yes
Maximum user weight vertical:	135.00 kg
Maximum lifetime:	10 years
Maximum number of persons:	1
Maximum temperature:	45 °C
Minimum user weight:	50.00 kg
Minimum temperature:	-35 °C

DIMENSIONS

Rope length:	1.80 m
--------------	--------

MATERIAL

Material:	Polyester, Polyamide, Steel, Aluminium
-----------	---