

Data sheet

IGNITE ION



GENERAL

Art. no.:	G-1130-M/XXL
EAN:	4030281222255
Standard:	EN 361:2002

E-class number:	40-02-01-02
Customs no.:	63079098

Data sheet

IGNITE ION

Our new all-round safety harness for all classical applications in construction and maintenance has above all one major feature due to simplified adjustment options in the chest and leg area as well as three different sizes: exceptional fit!

Even for users who rarely wear personal protective equipment against falls from height, the IGNITE ION is extremely easy to use and self-explanatory. The buckle by Fidlock in the chest area snaps magnetically and closes almost automatically. The two orange roping-up loops made of fabric are approved for joint use and equipped with abrasion indicator for maximum safety.

User-friendly, self-explanatory, safe:

- easy to put on and adjust
- very good fit
- large roping-up loops (chest) with wear indicator

FEATURES

Fall indicator

Shoulder or leg padding: yes

Belt strap coiler: yes

Hand-washing: 40 °C

Click buckles: yes

Max. service life: 6-8

Max. number of persons: 1

Max. rated load: 140 kg

Attachment Points:

dorsal attachment point, sternal attachment point

Patent

Temperature: from -35 °C to 45 °C

Area of application:

Construction / Roofer / Carpenter, Facade / Window Cleaning, High Rack, Lift Construction, Metal Construction, Mobile Work Platforms, Power Supplies / -Transmission / Telecommunications, Scaffolding

DIMENSIONS

Size:	M/XXL
Waist size:	800-1100mm
Weight:	1.257

MATERIAL

Material:	Aluminium, Polyester, Steel
Webbing material:	PES
Sternal attachment point material:	PES
Dorsal attachment point material:	AL
Material Click buckle:	V2A

Data sheet

PEANUT I



GENERAL

Art. no.: HSG-021-2,5-3

EAN: 4030281181927

Standard: based on EN 354
EN 360:2002
RFU CNB/P/11.060
RFU CNB/P/11.085

E-class number: 40-02-01-03

Customs no.: 84798997

Data sheet

PEANUT I

Ultra-compact fall protection device with FS 90 ST carabiner on anchoring. The Peanut is already equipped with the new One-4-All shock absorber and therefore approved for the weight class 50-135kg. 2.5 m length for use in scaffolding.

FEATURES

Fall indicator

Suitable for edges:	yes
---------------------	-----

Max. service life:	4-6
--------------------	-----

Max. number of persons:	1
-------------------------	---

Rated load:	135 kg
-------------	--------

Patent

Temperature:

from -35 °C to +45 °C

Suspension element:	Webbing
---------------------	---------

Area of application:	Scaffolding
----------------------	-------------

DIMENSIONS

Size:	2,5m
-------	------

Weight:	1.8
---------	-----

HARDWARE

Carabiner on anchoring point side:

FS 90 ST

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:

Polyamide, Polyester, Steel

Data sheet

DOUBLE-O TWIST



GENERAL

Art. no.:	H-176-TW	E-class number:	40-02-01-05
EAN:	4030281214120	Customs no.:	76169990
Standard:	EN 12275-H:2013 EN 362:2004		

Data sheet

DOUBLE-O TWIST

DOUBLE TWIST-O, the new generation of oval carabiner with 180 ° technology and smooth dual-locking mechanism for even more convenience and operational freedom.

With the new carabiner series DOUBLE, SKYLOTEC has now an answer for all those who work and climb left-handed or use both hands. With the innovative design (180° spring rotation), the sleeve that closes the gate can rotate in both directions. Conventional Twist/TriLock carabiners can be turned only to the right; therefore, they are more difficult to use for left-handers. Can be used in accordance with mountaineering and industry standard.

GENERAL

Internat. standard:	UIAA 121
---------------------	----------

FEATURES

Breaking load, major axis:
24 kN

Breaking load, minor axis:
8 kN

Breaking load, open:	8 kN
----------------------	------

Max. opening:	21 mm
---------------	-------

DIMENSIONS

Size:	109 x 58mm
-------	------------

Weight:	0.085
---------	-------

HARDWARE

Locking system:	Twist
-----------------	-------

MATERIAL

Material:	Aluminium
-----------	-----------

Data sheet

ROPE BAG



GENERAL

Art. no.:	ACS-0009-2	E-class number:	40-02-92-90
EAN:	4030281050575	Customs no.:	39232990

Data sheet

ROPE BAG

Classic rope bag for easy transportation and stowage of climbing ropes.

Max. rope length Ø11mm: 50m

FEATURES

Diameter:	300 mm
-----------	--------

Material load, max.:	15 kg
----------------------	-------

Area of application:	
----------------------	--

Wind Energy / Offshore Industry	
---------------------------------	--

DIMENSIONS

Size:	2
-------	---

Contents:	22 l
-----------	------

Weight:	0.31
---------	------

MATERIAL

Material:	Polyamide
-----------	-----------