



# CleanSpace® WORK Half Mask (inc. Fabric Head Harness)




PRODUCT CODE	CS3003WORK (Small), CS3004WORK (Medium), CS3005WORK (Large),
PRODUCT NAME	CleanSpace WORK Half Mask (inc. Fabric Head Harness)
DESCRIPTION	A CleanSpace WORK half mask (including a CleanSpace fabric head harness) is designed for use with the CleanSpace WORK power unit (CS3001WORK).
	A CleanSpace WORK half mask is made of soft silicone that readily moulds to the face and does not cause allergic dermatitis. The clips quickly and securely attach the CleanSpace Work half mask to the power unit.
	The CleanSpace fabric head harness attaches to connection points on the mask arms and can be removed for cleaning.
	A CleanSpace WORK half mask (including a CleanSpace fabric head harness) is NOT certified intrinsically safe.
APPROVALS	Standard & Classification
	EN12942:1998+A2:2008 TM3 AS/NZS1716: 2012 PAPR-P3 (P2 with Half Mask)  IP Rating 66
FEATURES	<ul> <li>Lightweight, comfortable and durable</li> <li>Soft silicone that readily molds to the face</li> <li>Available in 3 sizes - Small, Medium and Large - to facilitate a good seal and a comfortable fit</li> <li>Transparent to assist with communication</li> <li>Compatible with most cleaning and disinfection protocols</li> <li>Easily removable exhalation valve for cleaning</li> <li>Fit Test adaptor available for TSI Portacount™ fit testing</li> </ul>
SPECIFICATIONS	<ul> <li>Product Weight: CS3003WORK:147 g, CS3004WORK:153 g, CS3005WORK:169 g</li> <li>Product Dimensions: 170mm x 130mm x 70mm (approx)</li> <li>Head Harness Product Weight: 29 g</li> </ul>
MATERIALS	Silicone face piece   nylon mask release clips   polycarbonate exhalation valve   silicone leaf valve (Head Harness Materials: Polyester   Elastic   High Strength Silicone )

Australia (Head Office): +61 2 8436 4000 | sales@cleanspacetechnology.com Uncontrolled if downloaded or printed from the internet.





#### **DATA SHEET**





## CLEANING, USE & STORAGE CONDITIONS

- Cleaning: warm soapy water and soft, lint-free cloth or industrial washer
- · Do not use solvents, hot water, bleaching or chemical agents
- Use temperature range: -10°C to +45°C (14°F to +113°F) at < 90% relative humidity
- Storage conditions: +10°C to +30°C (+50°F to +86°F) at < 75% relative humidity
- Store away from direct sunlight, grease and oil

#### **APPLICATIONS**

Suitable for environments which require respiratory protection against airborne particulate contaminates.

Examples (use is not limited to these examples):

- Construction Cutting and grinding concrete, stone, brickwork, steel; sanding plaster, handing cement or other fine dusts
- Woodwork Cutting, turning or sanding timber
- Agriculture mowing, reaping and mulching operations; processing or handling animal feeds, grain or other dusty substances

The CleanSpace WORK Sytem (CS3000WORK) with the CleanSpace WORK half mask is suitable for applications where decontaminations showers¹ are used.

Note 1: For use in decontamination showers use the CleanSpace HALO head harness (CS3008). The CleanSpace fabric head harness is not suitable for decontamination shower use.

#### LIMITATIONS

CleanSpace respirators are air filtering, fan assisted, positive pressure systems and designed to be worn in environments where there is sufficient oxygen to breathe safely. Do not use CleanSpace WORK in environments that are immediately dangerous to life or health (IDLH), to protect against gases/vapours, or in oxygen enriched or deficient atmospheres.

CleanSpace WORK half masks are NOT suitable for intrinsically safe certified operations.

### EDUCATION

Contact sales@cleanspacetechnology.com or visit the CleanSpace website for details.

#### WARRANTY

Visit <a href="www.cleanspacetechnology.com/warranty">www.cleanspacetechnology.com/warranty</a> to read important Warranty information and complete the Warranty Registration Online Form for CleanSpace Products. Consumable parts are warranted up to the point of use, provided they have been stored correctly and are within their expiry date.

CleanSpace recommends filters are replaced regularly.

